



### Intrusion Alarm Systems

## Recessed 3/4" steel door - GE Sensors

#### Resources

[> Product Information](#)

#### Buy

[> Where To Buy](#)

#### Related

##### Products/Accessories

[> Recessed 1225](#)  
[> Recessed 1015](#)  
[> Recessed 1058](#)  
[> Recessed 1065](#)  
[> Recessed 1072](#)  
[> Recessed 1075](#)  
[> Recessed 1078](#)  
[> Recessed 1078CT](#)  
[> Recessed 1078T](#)  
[> Recessed 1075T](#)  
[> Recessed 1125](#)  
[> Recessed 1125T](#)  
[> Recessed 1275](#)  
[> Recessed R1075](#)  
[> Recessed R1078/R1078C](#)  
[> Recessed R1125](#)  
[> Recessed R1125T](#)  
[> Recessed 1055](#)

### Description

The Sentrol 1078 Series Steel Door contacts are designed specifically for use in the steel doors commonly found in commercial building applications. The unique housing design features a rugged unibody construction with flexible ribbed sides for quick, secure installation without gluing. The magnet housing isolates the magnet from the surrounding steel for maximum gap distances, both make and break.



An optional Rare Earth magnet is available. It is designed for use in metal entry/exit doors with a channel in the top of the door. The magnet eliminates the need to cut a mounting hole in the door channel. The flexible magnet housing can be compressed to accommodate a variety of channel widths for quick, easy installation.

### Features and Benefits

- 3/4" diameter for easier drilling in metal
- Self-lock mounting
- Rugged construction
- Attractive, added security of recessed installation

